

opti strap provides easy strap loading with auto re-feed and loop ejection for applications that require higher or more exact tensioning. Electronically-controlled tension is consistently exact in one simple operation using polyester strap.



Benefits:

- ☐ Fast Cycle Speed
- ☐ Utilizes high strength polyester strap
- ☐ Digital thermostat for consistent temperature
- ☐ Separate controls for:
 - strap feeding, tightening and tensioning
- ☐ Modular / Portable design
- ☐ Solid state controls allow easy troubleshooting
- ☐ Lubrication-Free operation
- ☐ Low maintenance
- ☐ Reliable and durable

Features:

Electrical	110V, 1PH, 60 HZ, .7KVA	Weight : 683 lbs	
Dimensions	Overall Width: 105" - Overall Height: 118.5" Overall Depth: 24" – Std Arch Size: 39.5" x 104"	Speed: 3.2 sec/strap	Tension: 0-175 lbs

Summary:

- **Guiding Mechanism**
- **Rapid Speed**
- **Reliable Operation**
- **Simple Maintenance**
- **Tension Adjustment**
- **Durable Mechanism**
- **Easy Strap Change**
- **Flexible Operation**
- ensures strap seal is in proper alignment
- 3.2 sec / cycle
- simple and durable operating mechanism
- no lubrication required – easily adjustable
- fully adjustable - 0-175 lbs
- designed to operate 24/7/365
- convenient loading and unloading of the strapping coil
- applicable in manual, semi-automated or automated Systems

Additional Features:

Pool Pulse Control System • Durable Sealing Mechanism • Quick Heat up Time • Programmable Heater Design
Sturdy Arch Design • Solid State Controls • Setup Panel and Diagnostic Display • Simple Operator Controls